

I **COMPRESSORI SILENT 2** sono proposti nelle versioni con motori da 4 a 10 Hp e presentano le seguenti caratteristiche:

- silenziatore in aspirazione;
- scheda elettronica di auto diagnosi e comando;
- contatore;
- manometro con glicerina;
- polmone smorzante;
- rubinetto di spurgo;
- ventilazione forzata per l'abbattimento della temperatura interna;
- termostati di controllo della temperatura;
- valvola di sicurezza;
- elettrovalvola per lo scarico della testa.

SILENT 2 COMPRESSORS are proposed in versions with motors from 4 to 10 Hp and they have the following features:

- silencer in suction air;
- electronic self-diagnosis and control card;
- hour-counter;
- pressure gauge with glycerine;
- damping receiver;
- drain valve;
- forced ventilation to reduce internal temperature;
- thermostat for temperature control;
- safety valve;
- solenoid valve for head discharge.



SILENT K50 T10



Prestazioni | Performance

Nome Name	Codice Code	Gruppo Pump	Serbatoio Tank	Potenza Power	Cilindri Cylinder	Press. max. Max. press.	Lubrific. Lubric.	N° Giri RPM	Aria aspirata Air displac.	Tensione freq. Voltage freq.	Peso Weight	Dimensioni Dimensions	dB(A)	Cod. a barre EAN code
			L	HP / kW	n.	bar / PSI			l/min. / CFM	Volt / Hz	kg / lbs	LxPxX / WxDxH		
SILENT K25 T4	SGOM601SHA	K25	3	4/3	2	11/160	YES	1200	495/17,5	400/50	157/346,1	870x640x1250	65	8028403011371
SILENT K25 T4 SD	SGOM605SHA	K25	3	4/3	2	11/160	YES	1200	495/17,5	400/50	162/357,1	870x640x1250	65	8028403011388
SILENT K30 T5,5	SL0M701SHA	K30	3	5,5/4	2	11/160	YES	1000	727/25,6	400/50	178/392,4	870x640x1250	65	8028403011395
SILENT K30 T5,5 SD	SL0M705SHA	K30	3	5,5/4	2	11/160	YES	1000	727/25,6	400/50	183/403,4	870x640x1250	65	8028403011401
SILENT K30 T7,5	SL0M801SHA	K30	3	7,5/5,5	2	11/160	YES	1200	872/31	400/50	190/418,8	870x640x1250	65	8028403011418
SILENT K30 T7,5 SD	SL0M805SHA	K30	3	7,5/5,5	2	11/160	YES	1200	872/31	400/50	195/430	870x640x1250	68	8028403011425
SILENT K50 T10	SMOM901SHA_	K50	3	10/7,5	2	11/160	YES	1000	1074/38	400/50	228/502,6	870x640x1250	68	8028403011432
SILENT K50 T10 SD	SMOM905SHA_	K50	3	10/7,5	2	11/160	YES	1000	1074/38	400/50	233/513,6	870x640x1250	68	8028403011449
Pressione massima 13 bar / Max pressure 13 bar														
SILENT K25 T4	SGOM601SHA201	K25	3	4/3	2	13/189	YES	1015	420/14,8	400/50	157/346,1	870x640x1250	65	8028403011456
SILENT K25 T4 SD	SGOM605SHA202	K25	3	4/3	2	13/189	YES	1015	420/14,8	400/50	162/357,1	870x640x1250	65	8028403011463
SILENT K30 T5,5	SL0M701SHA203	K30	3	5,5/4	2	13/189	YES	850	620/21,9	400/50	178/392,4	870x640x1250	65	8028403011470
SILENT K30 T5,5 SD	SL0M705SHA204	K30	3	5,5/4	2	13/189	YES	850	620/21,9	400/50	183/403,4	870x640x1250	65	8028403011487
SILENT K30 T7,5	SL0M801SHA205	K30	3	7,5/5,5	2	13/189	YES	900	660/23,3	400/50	190/418,8	870x640x1250	65	8028403011494
SILENT K30 T7,5 SD	SL0M805SHA206	K30	3	7,5/5,5	2	13/189	YES	900	660/23,3	400/50	195/430	870x640x1250	65	8028403011500
SILENT K50 T10	SMOM901SHA207_	K50	3	10/7,5	2	13/189	YES	800	857/30,3	400/50	228/502,6	870x640x1250	68	8028403011517
SILENT K50 T10 SD	SMOM905SHA208_	K50	3	10/7,5	2	13/189	YES	800	857/30,3	400/50	233/513,6	870x640x1250	68	8028403011524